

## Features:

- Reliable power in a cost-efficient machine.
- Packed with quality, performance and serviceability.
- · Wide variety of applications.
- Small package for effortless towing and maneuverability.
- Spin-on separator element expedites service and maintenance.
- Cool-box airflow design directs heat away from the unit to prolong life and minimize dust recirculation.
- Polymer canopy combines strength with easy-access to routine service items.

## Specifications:

MODEL	C185
COMPRESSOR ROTARY SCREW/SINGLE-STAGE	
Free-Air Delivery – cfm (m³/min)	185 (5.24)
Rated Operating Pressure – psig (bar)	100 (6.90)
Pressure Range – psig (bar)	70 - 125 (4.8 - 8.6)
Air Discharge Outlet NPT Size – in (mm)	0.75 (19)
Air Discharge Outlet Quantity	2
Fuel Tank Capacity – gal (L)	32 (121)
ENGINE	
Make/Model	Kubota V2403T
Emission Tier Level	2
Number of Cylinders	4
Displacement – L (cu in)	2.4 (148.5)
Rated Speed – rpm	2550
Idle Speed – rpm	1700
Bhp @ Rated Speed (kW)	62.4 (46.5)
Electrical – volts	12 V
Hours of Operation @ Full Load	11.6
DIMENSIONS WITH RUNNING GEAR	
Length – in (mm)	137.2 (3485)
Width – in (mm)	68.5 (1740)
Height – in (mm)	67.5 (1715)
Track Width – in (mm)	60 (1524)
Tire Size – in	13
Shipping Weight – w/o fuel – lb (kg)	2094 (950)
Working Weight – w fuel – lb (kg)	2333 (1058)

<sup>\*</sup>In Accordance to ISO1217 1996 Annexure E

## MAKE POWER MOVES.

DoosanPowerMoves.com | 1800 103 2869